

Article number 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Date printed 01.02.2018, Revision 09.05.2016

Version 01

Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier**2K-Gel Flex Part A****Article number: 110118****1.2 Relevant identified uses of the substance or mixture and uses advised against****1.2.1 Relevant uses**

Adhesive

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet**Company**

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR
 Scheveninger Str. 16
 12359 Berlin
 Phone Tel: 030 6814874
 Fax Fax: 030 68081018
 Homepage www.ber-fix.de
 E-mail info@berfix.de

Address enquiries to**Technical information**info@berfix.de**Safety Data Sheet**sdb@chemiebuero.de**1.4 Emergency telephone number****Advisory body**

+49 (0) 89-19240

Company
SECTION 2: Hazards identification
2.1 Classification of the substance or mixture

No classification.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms

none

Hazard statements

none

Special labelling

EUH202 Cyanoacrylate. Danger. Bonds skin and eyes in seconds. Keep out of the reach of children.

2.3 Other hazards**Human health dangers**

People who are allergic to cyanoacrylates should avoid the use of the product.

Other hazards

Further hazards were not determined with the current level of knowledge.

Article number 110118
Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR
12359 Berlin

Date printed 01.02.2018, Revision 09.05.2016

Version 01

Page 2 / 8

SECTION 3: Composition / Information on ingredients

Product-type:

The product is a mixture.

Range [%]	Substance
80 - < 100	2-methoxyethyl 2-cyanoacrylate CAS: 27816-23-5, EINECS/ELINCS: 248-670-5
1 - < 10	Dimethyl siloxane, reaction product with silica CAS: 67762-90-7
0,01 - < 0,1	1,4-Dihydroxybenzene CAS: 123-31-9, EINECS/ELINCS: 204-617-8, EU-INDEX: 604-005-00-4 GHS/CLP: Acute Tox. 4: H302 - Eye Dam. 1: H318 - Skin Sens. 1B: H317 - Muta. 2: H341 - Carc. 2: H351 - Aquatic Acute 1: H400 - Aquatic Chronic 1: H410, M = 10

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Change soaked clothing.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Do not open bonded eyelids forcibly and without any special care. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Seek medical advice immediately.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.
Forward this sheet to the doctor.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Foam, dry powder, water spray jet, carbon dioxide.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

5.3 Advice for firefighters

Use self-contained breathing apparatus.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Article number 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Date printed 01.02.2018, Revision 09.05.2016

Version 01

Page 3 / 8

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Pick up with absorbent material (e.g. sand, universal absorbent, diatomaceous earth).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Use only in well-ventilated areas.

Wash hands before breaks and after work.
Use barrier skin cream.
Do not eat, drink or smoke when using this product.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.
Do not use metal containers.

Protect from heat/overheating.
Keep in a cool place. Store in a dry place.
Recommended storage temperature: +5°C - +25°C

7.3 Specific end use(s)

This product is not recommended for use in joints which will be in contact with either pure oxygen or steam.

SECTION 8: Exposure controls / personal protection**8.1 Control parameters**

Ingredients with occupational
exposure limits to be monitored (GB)

Substance
2-methoxyethyl 2-cyanoacrylate
CAS: 27816-23-5, EINECS/ELINCS: 248-670-5
Long-term exposure: (like CAS 137-05-3)
Short-term exposure (15-minute): 0,3 ppm, 1,4 mg/m ³
1,4-Dihydroxybenzene
CAS: 123-31-9, EINECS/ELINCS: 204-617-8, EU-INDEX: 604-005-00-4
Long-term exposure: 0,5 mg/m ³

Article number 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Date printed 01.02.2018, Revision 09.05.2016

Version 01

Page 4 / 8

8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation.
Eye protection	safety glasses (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. > 0,4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).
Skin protection	light protective clothing
Other	Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier.
Respiratory protection	No dangerous reactions known if used as directed.
Thermal hazards	not applicable
Delimitation and monitoring of the environmental exposition	Comply with applicable environmental regulations limiting discharge to air, water and soil.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Form	liquid
Color	colourless
Odor	odourless
Odour threshold	not determined
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	74 - 76
Flash point [°C]	not applicable
Flammability (solid, gas) [°C]	not determined
Lower explosion limit	not applicable
Upper explosion limit	not applicable
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	not determined
Density [g/ml]	1,06 (20 °C / 68,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	virtually insoluble
Partition coefficient [n-octanol/water]	not determined
Viscosity	not determined
Relative vapour density determined in air	not determined
Evaporation speed	not determined
Melting point [°C]	not determined
Autoignition temperature [°C]	not determined
Decomposition temperature [°C]	not determined

9.2 Other information

none

SECTION 10: Stability and reactivity**10.1 Reactivity**

No dangerous reactions known if used as directed.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

Article number 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR
12359 Berlin

Date printed 01.02.2018, Revision 09.05.2016

Version 01

Page 5 / 8

10.3 Possibility of hazardous reactions

Reactions with acids, alkalies and oxidizing agents.

Reactions with reducing agents.

Exothermic polymerisation or reactions with active-hydrogen agents (including water) under the influence of alkalies, acids and some kind of metallic salts.

10.4 Conditions to avoid

Strong heating.

10.5 Incompatible materials

See SECTION 10.3.

10.6 Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Substance
Dimethyl siloxane, reaction product with silica, CAS: 67762-90-7
LD50, dermal, Rat: > 2000 mg/kg bw.
LD50, oral, Rat: > 5000 mg/kg bw.
LC0, inhalative, Rat: 0,139 mg/l/4h.

Serious eye damage/irritation	Based on the available information, the classification criteria are not fulfilled.
Skin corrosion/irritation	Based on the available information, the classification criteria are not fulfilled.
Respiratory or skin sensitisation	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — single exposure	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	

Toxicological data of complete product are not available.

SECTION 12: Ecological information

12.1 Toxicity

Substance
Dimethyl siloxane, reaction product with silica, CAS: 67762-90-7
LC50, (96h), Brachidanio rerio: > 10000 mg/l.
EC50, (24h), Daphnia magna: > 1000 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	not determined
Behaviour in sewage plant	not determined
Biological degradability	Hydroquinone (CAS 123-31-9) 75 - 81% (method C.4-E)

Article number 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Date printed 01.02.2018, Revision 09.05.2016

Version 01

Page 6 / 8

12.3 Bioaccumulative potential

Product has having no bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Do not discharge product unmonitored into the environment.
The product is insoluble in water.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Coordinate disposal with the disposal contractor/authorities if necessary.

Waste no. (recommended)

080410

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Contaminated packing should be disposed of as product waste.

Waste no. (recommended)150102
150104**SECTION 14: Transport information****14.1 UN number**

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.2 UN proper shipping name

Transport by land according to ADR/RID NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with IMDG NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

Article number 110118
Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR
12359 Berlin

Date printed 01.02.2018, Revision 09.05.2016

Version 01

Page 7 / 8

14.3 Transport hazard class(es)

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to ADR/RID not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with IMDG not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS DOT-Classification, ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2017).

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

- Observe employment restrictions for people no

- VOC (2010/75/CE) not determined

15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

Article number 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Date printed 01.02.2018, Revision 09.05.2016

Version 01

Page 8 / 8

SECTION 16: Other information**16.1 Hazard statements
(SECTION 03)**

H410 Very toxic to aquatic life with long lasting effects.
 H400 Very toxic to aquatic life.
 H351 Suspected of causing cancer.
 H341 Suspected of causing genetic defects.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H302 Harmful if swallowed.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 ATE = acute toxicity estimate
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV@/TWA = Threshold limit value – time-weighted average
 TLV@STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Customs Tariff not determined
Classification procedure
Modified position none

Copyright: Chemiebüro®

Artikelnummer 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Druckdatum 01.02.2018, Überarbeitet am 09.05.2016

Version 01

Seite 1 / 9

ABSCHNITT 1: Bezeichnung des Stoffs bzw. des Gemischs und des Unternehmens
1.1 Produktidentifikator

2K-Gel Flex Part B

Artikelnummer: 110118

1.2 Relevante identifizierte Verwendungen des Stoffs oder Gemischs und Verwendungen, von denen abgeraten wird
1.2.1 Relevante Verwendungen

Klebstoff
Aktivator

1.2.2 Verwendungen, von denen abgeraten wird

Keine bekannt

1.3 Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt

Firma	Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR Scheveninger Str. 16 12359 Berlin Telefon Tel: 030 6814874 Fax Fax: 030 68081018 Homepage www.ber-fix.de E-Mail info@berfix.de
--------------	---

Auskunftgebender Bereich

Technische Auskunft	info@berfix.de
Sicherheitsdatenblatt	sdb@chemiebuero.de

1.4 Notrufnummer

Beratungsstelle	+49 (0) 89-19240
Firma	

ABSCHNITT 2: Mögliche Gefahren
2.1 Einstufung des Stoffs oder Gemischs

Keine Einstufung

2.2 Kennzeichnungselemente

Das Produkt ist gemäß Verordnung (EG) 1272/2008 (CLP) nicht kennzeichnungspflichtig.

Gefahrenpiktogramme	keine
Signalwort	keine
Gefahrenhinweise	keine

2.3 Sonstige Gefahren

Andere Gefahren	keine
------------------------	-------

Artikelnummer 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Druckdatum 01.02.2018, Überarbeitet am 09.05.2016

Version 01

Seite 2 / 9

ABSCHNITT 3: Zusammensetzung / Angaben zu Bestandteilen**Produktart:**

Bei dem Produkt handelt es sich um ein Gemisch.

Gehalt [%]	Bestandteil
1 - 10	Silicone und Siloxane, Reaktionsprodukte mit Siliciumdioxid
	CAS: 67762-90-7

Bestandteilekommentar

Keine gefährlichen Bestandteile enthalten.
SVHC Liste (Candidate List of Substances of Very High Concern for authorisation): Enthält keine oder unter 0,1% der gelisteten Stoffe.

ABSCHNITT 4: Erste-Hilfe-Maßnahmen**4.1 Beschreibung der Erste-Hilfe-Maßnahmen**

Allgemeine Hinweise	Benetzte Kleidung wechseln.
Nach Einatmen	Nicht erforderlich unter normalen Bedingungen. Für Frischluft sorgen.
Nach Hautkontakt	Bei Berührung mit der Haut mit Wasser und Seife abwaschen. Bei andauernder Hautreizung Arzt aufsuchen.
Nach Augenkontakt	Einige Minuten lang behutsam mit Wasser ausspülen. Eventuell vorhandene Kontaktlinsen nach Möglichkeit entfernen. Weiter ausspülen. Bei anhaltender Augenreizung: Ärztlichen Rat einholen/ärztliche Hilfe hinzuziehen.
Nach Verschlucken	Mund ausspülen und reichlich Wasser nachtrinken. Kein Erbrechen einleiten. Ärztlicher Behandlung zuführen.

4.2 Wichtigste akute oder verzögert auftretende Symptome und Wirkungen

Keine Informationen verfügbar.

4.3 Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung

symptomatisch behandeln
Sicherheitsdatenblatt dem Arzt zur Verfügung stellen.

ABSCHNITT 5: Maßnahmen zur Brandbekämpfung**5.1 Löschmittel**

Geeignete Löschmittel	Alkoholbeständiger Schaum. Löschpulver. Kohlendioxid (CO ₂).
Ungeeignete Löschmittel	Wasservollstrahl

5.2 Besondere vom Stoff oder Gemisch ausgehende Gefahren

Gefahr der Bildung toxischer Pyrolyseprodukte.

5.3 Hinweise für die Brandbekämpfung

Explosions- und Brandgase nicht einatmen.
Umgebungsluftunabhängiges Atemschutzgerät verwenden.
Brandrückstände und kontaminiertes Löschwasser müssen entsprechend den örtlichen behördlichen Vorschriften entsorgt werden.

ABSCHNITT 6: Maßnahmen bei unbeabsichtigter Freisetzung**6.1 Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren**

Für ausreichende Lüftung sorgen.
Persönliche Schutzkleidung verwenden.

Artikelnummer 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Druckdatum 01.02.2018, Überarbeitet am 09.05.2016

Version 01

Seite 3 / 9

6.2 Umweltschutzmaßnahmen

Keine besonderen Maßnahmen erforderlich.

6.3 Methoden und Material für Rückhaltung und Reinigung

Mit flüssigkeitsbindendem Material (z.B. Universalbindemittel) aufnehmen.
Das aufgenommene Material vorschriftsmäßig entsorgen.

6.4 Verweis auf andere Abschnitte

Siehe ABSCHNITTE 8+13

ABSCHNITT 7: Handhabung und Lagerung

7.1 Schutzmaßnahmen zur sicheren Handhabung

Bei sachgemäßer Verwendung keine besonderen Maßnahmen erforderlich.

Bei Verwendung dieses Produkts nicht essen, trinken oder rauchen.
Kontaminierte Arbeitskleidung soll am Arbeitsplatz verbleiben.
Kontaminierte Kleidung ausziehen und vor erneutem Tragen waschen.
Vorbeugender Hautschutz durch Hautschutzsalbe.
Vor den Pausen und bei Arbeitsende Hände waschen.

7.2 Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten

Nur im Originalbehälter aufbewahren.
Eindringen in den Boden sicher verhindern.
Keine Informationen verfügbar.
Keine besonderen Maßnahmen erforderlich.

Lagerklasse (TRGS 510)

LGK 10-13

7.3 Spezifische Endanwendungen

Siehe Verwendung des Produktes, ABSCHNITT 1.2

ABSCHNITT 8: Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstung

8.1 Zu überwachende Parameter

Arbeitsplatzgrenzwerte (DE)

nicht relevant

Artikelnummer 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Druckdatum 01.02.2018, Überarbeitet am 09.05.2016

Version 01

Seite 4 / 9

8.2 Begrenzung und Überwachung der Exposition

Zusätzliche Hinweise zur Gestaltung technischer Anlagen Für ausreichende Be- und Entlüftung am Arbeitsplatz sorgen.

Augenschutz Dicht schliessende Schutzbrille. (EN 166:2001)

Handschutz Bei den Angaben handelt es sich um Empfehlungen. Für weitere Informationen bitte den Handschuhlieferanten kontaktieren.
bei Spritzkontakt:
Nitrilkautschuk, >120 min (EN 374-1/-2/-3).
Bei Dauerkontakt:
Nitrilkautschuk, >480 min (EN 374-1/-2/-3).

Körperschutz Leichte Schutzkleidung

Sonstige Schutzmaßnahmen Die persönliche Schutzausrüstung ist in ihrer Ausführung in Abhängigkeit von Konzentration und Menge arbeitsplatzspezifisch auszuwählen. Die Chemikalienbeständigkeit der Schutzmittel sollte mit deren Lieferanten abgeklärt werden.
Berührung mit den Augen und der Haut vermeiden.

Atenschutz Atenschutz bei hohen Konzentrationen.
Kurzzeitig Filtergerät, Filter A. (DIN EN 14387)

Thermische Gefahren Keine Informationen verfügbar.

Begrenzung und Überwachung der Umweltexposition Keine Informationen verfügbar.

ABSCHNITT 9: Physikalische und chemische Eigenschaften

9.1 Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften

Form	flüssig
Farbe	farblos
Geruch	charakteristisch
Geruchsschwelle	nicht bestimmt
pH-Wert	nicht anwendbar
pH-Wert [1%]	nicht anwendbar
Siedebeginn/Siedebereich [°C]	nicht bestimmt
Flammpunkt [°C]	< 160
Entzündbarkeit (fest, gasförmig) [°C]	nicht bestimmt
Untere Entzündbarkeits- oder Explosionsgrenze	nicht bestimmt
Obere Entzündbarkeits- oder Explosionsgrenze	nicht bestimmt
Oxidierende Eigenschaften	nein
Dampfdruck [kPa]	nicht bestimmt
Relative Dichte [g/ml]	nicht bestimmt
Schüttdichte [kg/m³]	nicht anwendbar
Löslichkeit in Wasser	nicht bestimmt
Verteilungskoeffizient [n-Oktanol/Wasser]	nicht bestimmt
Viskosität	nicht bestimmt
Dampfdichte	nicht bestimmt
Verdampfungsgeschwindigkeit	nicht bestimmt
Schmelzpunkt/Gefrierpunkt [°C]	nicht bestimmt
Selbstentzündungstemperatur [°C]	nicht bestimmt
Zersetzungstemperatur [°C]	nicht bestimmt

9.2 Sonstige Angaben

keine

Artikelnummer 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Druckdatum 01.02.2018, Überarbeitet am 09.05.2016

Version 01

Seite 5 / 9

ABSCHNITT 10: Stabilität und Reaktivität**10.1 Reaktivität**

Siehe ABSCHNITT 10.3.

10.2 Chemische Stabilität

Unter normalen Umgebungsbedingungen (Raumtemperatur) stabil.

10.3 Möglichkeit gefährlicher Reaktionen

Reaktionen mit starken Oxidationsmitteln.

Reaktionen mit Sauerstoff.

10.4 Zu vermeidende Bedingungen

Keine Informationen verfügbar.

10.5 Unverträgliche Materialien

Starke Oxidationsmittel

10.6 Gefährliche Zersetzungsprodukte

Keine gefährlichen Zersetzungsprodukte bekannt.

ABSCHNITT 11: Toxikologische Angaben**11.1 Angaben zu toxikologischen Wirkungen****Akute Toxizität**

Bestandteil
Silicone und Siloxane, Reaktionsprodukte mit Siliciumdioxid, CAS: 67762-90-7
LD50, dermal, Ratte: > 2000 mg/kg bw.
LD50, oral, Ratte: > 5000 mg/kg bw.
LC0, inhalativ, Ratte: 0,139 mg/l/4h.

Schwere Augenschädigung/-reizung Aufgrund der verfügbaren Informationen sind die Einstufungskriterien nicht erfüllt.**Ätz-/Reizwirkung auf die Haut** Aufgrund der verfügbaren Informationen sind die Einstufungskriterien nicht erfüllt.**Sensibilisierung der Atemwege/Haut** Aufgrund der verfügbaren Informationen sind die Einstufungskriterien nicht erfüllt.**Spezifische Zielorgan-Toxizität bei einmaliger Exposition** Aufgrund der verfügbaren Informationen sind die Einstufungskriterien nicht erfüllt.**Spezifische Zielorgan-Toxizität bei wiederholter Exposition** Aufgrund der verfügbaren Informationen sind die Einstufungskriterien nicht erfüllt.**Mutagenität** Aufgrund der verfügbaren Informationen sind die Einstufungskriterien nicht erfüllt.**Reproduktionstoxizität** Aufgrund der verfügbaren Informationen sind die Einstufungskriterien nicht erfüllt.**Karzinogenität** Aufgrund der verfügbaren Informationen sind die Einstufungskriterien nicht erfüllt.**Aspirationsgefahr** Aufgrund der verfügbaren Informationen sind die Einstufungskriterien nicht erfüllt.**Allgemeine Bemerkungen**

Toxikologische Daten des Gesamtproduktes liegen nicht vor.

ABSCHNITT 12: Umweltbezogene Angaben**12.1 Toxizität**

Bestandteil
Silicone und Siloxane, Reaktionsprodukte mit Siliciumdioxid, CAS: 67762-90-7
LC50, (96h), Brachidanio rerio: > 10000 mg/l.
EC50, (24h), Daphnia magna: > 1000 mg/l.

Artikelnummer 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Druckdatum 01.02.2018, Überarbeitet am 09.05.2016

Version 01

Seite 6 / 9

12.2 Persistenz und Abbaubarkeit

Verhalten in Umweltkompartimenten

Verhalten in Kläranlagen

Biologische Abbaubarkeit

12.3 Bioakkumulationspotenzial

Keine Informationen verfügbar.

12.4 Mobilität im Boden

Keine Informationen verfügbar.

12.5 Ergebnisse der PBT- und vPvB-Beurteilung

Keine Informationen verfügbar.

12.6 Andere schädliche Wirkungen

Produkt nicht unkontrolliert in die Umwelt und in die Kanalisation gelangen lassen.

Ökotoxikologische Daten des Gesamtproduktes liegen nicht vor.

ABSCHNITT 13: Hinweise zur Entsorgung

13.1 Verfahren zur Abfallbehandlung

Produktreste sind unter Beachtung der Abfallrichtlinie 2008/98/EG sowie nationalen und regionalen Vorschriften zu entsorgen. Für dieses Produkt kann keine Abfallschlüssel-Nummer gemäß europäischem Abfallkatalog (AVV) festgelegt werden, da erst der Verwendungszweck durch den Verbraucher eine Zuordnung erlaubt. Die Abfallschlüssel-Nummer ist innerhalb der EU in Absprache mit dem Entsorger festzulegen.

Produkt

Entsorgung mit den Entsorgern/ Behörden gegebenenfalls abstimmen.

AVV-Nr. (empfohlen)

080409* Klebstoff- und Dichtungsmassenabfälle, die organische Lösemittel oder andere gefährliche Stoffe enthalten.

Ungereinigte Verpackungen

Nicht kontaminierte Verpackungen können einem Recycling zugeführt werden.

Nicht reinigungsfähige Verpackungen sind wie der Stoff zu entsorgen.

AVV-Nr. (empfohlen)

150110* Verpackungen, die Rückstände gefährlicher Stoffe enthalten oder durch gefährliche Stoffe verunreinigt sind.

ABSCHNITT 14: Angaben zum Transport

14.1 UN-Nummer

Landtransport nach ADR/RID nicht anwendbar

Binnenschifffahrt (ADN) nicht anwendbar

Seeschifftransport nach IMDG nicht anwendbar

Lufttransport nach IATA nicht anwendbar

Artikelnummer 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Druckdatum 01.02.2018, Überarbeitet am 09.05.2016

Version 01

Seite 7 / 9

14.2 Ordnungsgemäße UN-Versandbezeichnung

Landtransport nach ADR/RID	KEIN GEFÄHRGUT
Binnenschifffahrt (ADN)	KEIN GEFÄHRGUT
Seeschifftransport nach IMDG	NOT CLASSIFIED AS "DANGEROUS GOODS"
Lufttransport nach IATA	NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transportgefahrenklassen

Landtransport nach ADR/RID	nicht anwendbar
Binnenschifffahrt (ADN)	nicht anwendbar
Seeschifftransport nach IMDG	nicht anwendbar
Lufttransport nach IATA	nicht anwendbar

14.4 Verpackungsgruppe

Landtransport nach ADR/RID	nicht anwendbar
Binnenschifffahrt (ADN)	nicht anwendbar
Seeschifftransport nach IMDG	nicht anwendbar
Lufttransport nach IATA	nicht anwendbar

14.5 Umweltgefahren

Landtransport nach ADR/RID	nein
Binnenschifffahrt (ADN)	nein
Seeschifftransport nach IMDG	nein
Lufttransport nach IATA	nein

14.6 Besondere Vorsichtsmaßnahmen für den Verwender

nicht anwendbar

Entsprechende Angabe unter ABSCHNITT 6 bis 8.

14.7 Massengutbeförderung gemäß Anhang II des MARPOL-Übereinkommens und gemäß IBC-Code

nicht anwendbar

Artikelnummer 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Druckdatum 01.02.2018, Überarbeitet am 09.05.2016

Version 01

Seite 8 / 9

ABSCHNITT 15: Rechtsvorschriften**15.1 Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch**

EU-VORSCHRIFTEN	1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2008/47/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014
TRANSPORT-VORSCHRIFTEN	ADR (2017); IMDG-Code (2017, 38. Amdt.); IATA-DGR (2017)
NATIONALE VORSCHRIFTEN (DE):	Gefahrstoffverordnung - GefStoffV 2016; Wasserhaushaltsgesetz - WHG; TRGS: 200, 220, 615, 900, 905.
- Wassergefährdungsklasse	2 (Selbsteinstufung)
- Störfallverordnung	nicht anwendbar
- Klassifizierung nach TA-Luft	nicht anwendbar
- GISBAU, Produktcode	nicht anwendbar
- Lagerklasse (TRGS 510)	LGK 10-13
- Beschäftigungsbeschränkungen	nicht anwendbar
- VOC (2010/75/EG)	< 3%
- Sonstige Vorschriften	nicht anwendbar

15.2 Stoffsicherheitsbeurteilung

Stoffsicherheitsbeurteilungen für Stoffe in dieser Mischung wurden nicht durchgeführt.

Artikelnummer 110118

Ber-Fix Klebstoffprodukte G.Häring & Ch.Franke GbR

12359 Berlin

Druckdatum 01.02.2018, Überarbeitet am 09.05.2016

Version 01

Seite 9 / 9

ABSCHNITT 16: Sonstige Angaben**16.1 Abkürzungen und Akronyme:**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 AVV = Abfallverzeichnis-Verordnung
 ATE = acute toxicity estimate
 BGI = Berufsgenossenschaftliche Informationen
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 LGK = Lagerklasse
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV@/TWA = Threshold limit value – time-weighted average
 TLV@STEL = Threshold limit value – short-time exposure limit
 TRGS = Technische Regeln für Gefahrstoffe
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative
 AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

16.2 Sonstige Angaben**Einstufungsverfahren****Geänderte Positionen**

keine

Das Dokument ist urheberrechtlich geschützt - Copyright: Chemiebüro® - Nutzungsbedingungen und Urheberrecht siehe www.chemiebuero.de. Tel. +49(0)941-646 353-0, E-mail info@chemiebuero.de

Gefahrstoffmanagementsystem - Betriebsanweisungen - leichtgemacht. Nähere Informationen unter www.sdbpool.de